

## Gear-Oil Leak Stop

### Description

Stops oil loss in transmissions that drip. Regenerates hardened plastic and rubber seals. No more environmentally pollutant oil patches. Prevents oil leaking onto clutches and prevents lubrication deficiency and transmission damage due to an insufficient quantity of oil.



### Properties

- prevents oil leaks and pollution of the environment
- increases operational reliability
- optimum lubrication under all operating conditions
- avoids oil leaking onto clutches
- prevents oil loss
- simple to use
- remedies leaks at shrunken or porous seals
- miscible with all commercially available gear oils

**and may be considered reliable, although not legally binding.**

### Technical data

Viscosity at 40 °C	642 mm <sup>2</sup> /s DIN 51562
Viscosity index	101 DIN ISO 2909
Flash point	66 °C DIN ISO 2592
Pour point	-27 °C DIN ISO 3016
Color number (ASTM)	3,5 DIN ISO 2049
Base	combination of additives
Color / appearance	blue
Density at 20 °C	0,92 g/ml
Odor	characteristic
Form	liquid

### Areas of application

For manual transmissions, power take-off and differential gears. **Note: Not suitable for DSG or automatic transmissions or differentials and motorbikes with wet clutches.**

### Application

One tube is sufficient for 1 litre of gear oil. The product can be added at any time. For best results, add every time the oil is changed.

### Available pack sizes

50 ml Tube plastic	21641
	E-P

### Our information is based on thorough research