

Product information

Speed Tec Gasoline

PI 46/10/15/2021



Description

A state-of-the-art, ash-free fuel additive for improving combustion and acceleration in partial load range. Compatible with all gasoline and additive qualities. Improves considerably vehicle acceleration.

Properties

- improves acceleration
- optimizes engine performance
- contains no organometallic compounds
- tested for the use with catalytic converters
- does not influence the octane number
- better drivability

Technical data

Base	Additive mixture in carrier fluid
Color / appearance	light brown
Density at 15 °C	0,825 g/cm ³
Flash point	>63 °C
Odor	characteristic
Form	liquid
Viscosity at 40 °C	<7 mm ² /s

Areas of application

Used as an additive in the fuel of all 2-stroke and 4-stroke gasoline engines, especially for motor vehicle engines. Also can be used in two-wheeled vehicles. For the improvement of vehicle acceleration and smooth operation.

Application

One 250 ml can is sufficient for max. 70 liters of gasoline fuel. Mix the contents of the can with the gasoline fuel. Mixing also takes place automatically.

Available pack sizes

250 ml Can sheet metal	21644
	D-E-P
250 ml Can sheet metal	2848
	GB-DK-FIN-N-S
250 ml Can sheet metal	20878
	JP
250 ml Can sheet metal	3720
	D-GB-I

Our information is based on thorough research and may be considered reliable, although not legally binding.

